



OFFICE



	6810 DAVOS Incasso/Recessed/Deckeneinbauversion Struttura/Frame/Rahmen Metallo e policarbonato Metal and polycarbonate/Metal und Polycarbonat Colore/Color/Farbe Bianco/White/Weiss Ottica/Optic/Linse Opale/Opal/Opal Driver/Driver/Treiber Incluso/Included/Inclusiv Alimentazione/Power supply/Transformator 220-240V AC		
	Potenza tot. ass. Total absorbed power Gesamt absorbiert Strom	20W	30W
	Lumen	1800 Warm white 1900 Natural white	2700 Warm white 2800 Natural white
	Lm/W@85°C	80 Warm white 90 Natural white	110 Warm white - 115 Natural white
	CRI TYP	>80	
	Tipo di raffreddamento Type of cooling/Kühlungsart	Passivo Passive/Passiv	
	Temperatura ambiente di funzionamento Operating ambient temp. Betriebsumgebungstemperatur	-10° + 45° C	
Tipo di garanzia Warranty type/Garantie Typ		Garanzia 5 anni 5 years/5 Jahre	

IP44 CE



  IP20 CE 	6837 DIVA		
	Lampada da parete/Wall lamp/Wandeleuchte		
	Struttura/Frame/Rahmen		
	Pressofusione in alluminio		
	Die-cast aluminium/AluminiumdruckgBlackiert		
	Colore/Color/Farbe		
	Bianco/White/Weiss		
	Ottica/Optic/Linse		
	Asimmetrica/Asymmetric/Asymmetrisch		
	Driver/Driver/Treiber		
	Incluso/Included/Inclusiv		
	Alimentazione/Power supply/Transformator		
220-240V AC			
Potenza tot. ass.		27W	41W
Total absorbed power			
Gesamt absorbierter Strom			
Lumen		2900 Warm Real Color	4300 Warm Real Color
		3000 Natural Real Color	4450 Natural Real Color
Lm/W@85°C		80 Warm white 90 Natural white	110 Warm white - 115 Natural white
CRI TYP		>90	
Tipo di raffreddamento		Passivo	
Type of cooling/Kühlungsart		Passive/Passiv	
Temperatura ambiente di funzionamento		-10° + 45° C	
Operating ambient temp.			
Betriebsumgebungstemperatur			
Tipo di garanzia		Garanzia 5 anni	
Warranty type/Garantie Typ		5 years/5 jahre	



6832 VIESTE

Incasso/Recessed/Deckeneinbauversion

Struttura/Frame/Rahmen

Metallo e policarbonato

Metal and polycarbonate

Metal und Polycarbonat

Colore/Color/Farbe

Bianco/White/Weiss

Ottica/Optic/Linse

Opale/Opal/Opal

Driver/Driver/Treiber

Incluso/Included/Inclusiv

Alimentazione/Power supply/Transformator

220-240V AC

IP40

CE



Potenza tot. ass.

*Total absorbed power
Gesamt absorbiert Strom*

Lumen

Lm/W@85°C

CRI TYP

Tipo di raffreddamento

Type of cooling/Kühlungsart

Temperatura ambiente di funzionamento

Operating ambient temp.

Betriebsumgebungstemperatur

Tipo di garanzia

Warranty type/Garantie Typ

15W

1350 Warm white
1500 Natural white

90 Warm white
100 Natural white

-10° + 45° C

20W

1800 Warm white
2000 Natural white

90 Warm white
100 Natural white

-10° + 50° C

30W

2700 Warm white
3000 Natural white

90 Warm white
100 Natural white

-10° + 50° C

>80

Passivo

Passive/Passiv

Garanzia 5 anni

5 years/5 Jahre



FABAS LUCE S.p.A.

Via Luigi Talamoni, 75
20861 BRUGHERIO (MB) Italy
Tel. 0039 039 214 22 06
0039 039 89 06 91
Fax 0039 039 214 22 08
www.fabasluce.it
info@fabasluce.it

FABAS LUCE GmbH

ATILED SHOWROOM
Franz Volk Strasse 5a
D - 77652 Offenburg
Tel. +49(0) 781 125 59 932
www.atiled.it
atiled.germany@fabasluce.com

CAF2017-08



8 019282 098430