



# PROFILE



# IP40


|                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>23W/m</b><br><br>  <b>OSRAM</b><br><small>Opto Semiconductors</small> | <b>6704 SHARON PLUS</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminiumium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Lumen</b><br><b>Lm/W@85°C</b><br><b>CRI TYP</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ | <b>23W/m</b><br><b>2400 Warm white - 2600 Natural white</b><br><b>110 Warm white - 115 Natural white</b><br><b>85</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>70 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre  |
| <b>23W/m</b><br><br>  <b>OSRAM</b><br><small>Opto Semiconductors</small> | <b>6404 SHARON RGB</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminiumium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm  | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ                                                       | <b>23W/m</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>70 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre                                                                                                           |
| <b>10W/m</b><br><br>  <b>OSRAM</b><br><small>Opto Semiconductors</small> | <b>6414 SABINE</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminiumium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm      | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Lumen</b><br><b>Lm/W@85°C</b><br><b>CRI TYP</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ | <b>10W/m</b><br><b>1000 Warm white - 1050 Natural white</b><br><b>105 Warm white - 110 Natural white</b><br><b>85</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>140 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre |
| <b>5W/m</b><br><br>  <b>OSRAM</b><br><small>Opto Semiconductors</small>  | <b>6427 EBAN</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminiumium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm        | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Lumen</b><br><b>Lm/W@85°C</b><br><b>CRI TYP</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ | <b>5W/m</b><br><b>490 Warm white - 520 Natural white</b><br><b>105 Warm white - 110 Natural white</b><br><b>85</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>70 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre     |



# IP65

|                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>23W/m</b>  <div> <b>CE</b>  <b>OSRAM</b><br/> <small>Opto Semiconductors</small> </div> | <b>6704 SHARON PLUS</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Lumen</b><br><b>Lm/W@85°C</b><br><b>CRI TYP</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ | <b>23W/m</b><br><b>2400 Warm white - 2600 Natural white</b><br><b>110 Warm white - 115 Natural white</b><br><b>85</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>70 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre  |
| <b>23W/m</b>  <div> <b>CE</b>  <b>OSRAM</b><br/> <small>Opto Semiconductors</small> </div> | <b>6404 SHARON RGB</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm  | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ                                                       | <b>23W/m</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>70 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre                                                                                                           |
| <b>10W/m</b>  <div> <b>CE</b>  <b>OSRAM</b><br/> <small>Opto Semiconductors</small> </div> | <b>6414 SABINE</b> Profilo / Profile / Profil<br><b>Struttura/Frame/Rahmen</b><br>Alluminio/Aluminium/Aluminium<br><b>Ottica/Optic/Linse</b><br>120° / 60°<br><b>Driver/Driver/Treiber</b><br>Escluso/Excluded/Nicht inklusiv<br><b>Alimentazione/Power supply/Transformator</b><br>24V DC<br><b>Taglio/Cut/Schneidbar</b><br>10 cm      | <b>Potenza tot. ass./Total absorbed power/Gesamt absorbierter Strom</b><br><b>Lumen</b><br><b>Lm/W@85°C</b><br><b>CRI TYP</b><br><b>Tipo di raffreddamento</b><br>Type of cooling/Kühlungsart<br><b>Temperatura ambiente di funzionamento</b><br>Operating ambient temp.<br>Betriebsumgebungstemperatur<br><b>Numero LED/LED number/Anzahl LED</b><br><b>Tipo di garanzia</b><br>Warranty type/Garantie Typ | <b>10W/m</b><br><b>1000 Warm white - 1050 Natural white</b><br><b>105 Warm white - 110 Natural white</b><br><b>85</b><br><b>Passivo</b><br>Passive/Passiv<br><b>-20° + 50° C</b><br><b>140 LED/m</b><br><b>Garanzia 5 anni</b><br>5 years/5 jahre |

## ACCESSORI / ACCESSORIES / ZUBEHÖR

|                                                                                  |                                                                                                                                                                                                                                                                                            |                                                                                                                                    |                                                                                    |
|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|
|  | <b>6402-06-000</b><br><b>Ottica 120° trasparente</b><br>Transparent optic 120°<br>Transparente Abdeckung 120°                                                                                                                                                                              | <b>Materiale</b><br>Material<br>Material                                                                                           | Policarbonato<br>Polycarbonate<br>Polycarbonat                                     |
|  | <b>6402-07-000</b><br><b>Ottica 120° satinata</b><br>Satinated optic 120°<br>Opale Abdeckung 120°                                                                                                                                                                                          | <b>Materiale</b><br>Material<br>Material                                                                                           | Policarbonato<br>Polycarbonate<br>Polycarbonat                                     |
|  | <b>6402-08-000</b><br><b>Ottica 60° trasparente</b><br>Transparent optic 60°<br>Transparente Abdeckung 60°                                                                                                                                                                                 | <b>Materiale</b><br>Material<br>Material                                                                                           | Policarbonato<br>Polycarbonate<br>Polycarbonat                                     |
|  | <b>IP40</b><br><b>6404-50-28</b><br><b>6404-50-27</b><br><b>6404-50-26</b><br><br><b>IP65</b><br><b>6404-50-21</b><br><b>6404-50-20</b><br><b>6404-50-19</b><br><br><b>Supporto in ottone cromato opaco</b><br>Brass bracket matt chromed<br>Halter für Profil aus Messing, matt verchromt | Dimensioni/Dimensions/Maße<br>Ø 30 x 315 mm<br>Ø 30 x 165 mm<br>Ø 30 x 65 mm<br><br>Ø 34 x 315 mm<br>Ø 34 x 165 mm<br>Ø 34 x 65 mm | <b>Materiale</b><br>Material<br>Material<br><br><br><br>Ottone<br>Brass<br>Messing |

## ACCESSORI IP65 / ACCESSORIES IP65 / ZUBEHÖR IP65

|                                                                                    |                                                                                                                                                                |                                          |      |
|------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|------|
|  | <b>6404-50-017</b><br><b>Giunto per connessioni IP68 a due vie</b><br>Joint for connection IP68 with two exits<br>Verbindungsbox IP 68 mit zwei Ausgängen      | <b>Materiale</b><br>Material<br>Material | PA66 |
|  | <b>6404-50-023</b><br><b>Giunto per connessioni IP68 a quattro vie</b><br>Joint for connection IP68 with four exits<br>Verbindungsbox IP 68 mit vier Ausgängen | <b>Materiale</b><br>Material<br>Material | PA66 |



**FABAS LUCE S.p.A.**  
Via Luigi Talamoni, 75  
20861 BRUGHERIO (MB) Italy  
Tel. 0039 039 214 22 06  
0039 039 89 06 91  
Fax 0039 039 214 22 08  
www.fabasluce.it  
info@fabasluce.it

**FABAS LUCE GmbH**  
ATILED SHOWROOM  
Franz Volk Strasse 5a  
D - 77652 Offenburg  
Tel. +49(0) 781 125 59 932  
www.atiled.it  
atiled.germany@fabasluce.com

CAF2017-10



8 019282 098454